

MALÅ Easy Locator Pro WideRange HDR

GROUND PENETRATING RADAR

The professional's choice for utility mapping

Now introducing a unique addition to the EL product family – MALÅ EL Pro WideRange HDR, with the widest GPR antenna bandwidth available for utility detection, on the market. Ultra-fast simultaneous high-resolution data acquisition for both shallow and deep targets – all in one solution.

The new cart has improved stability and folding mechanics. In conjunction with alternative wheel options, new controller tray, battery compartment with more battery space and a better lock, the utility locating becomes more efficient. In conjunction with the EL Pro WideRange HDR, Object Mapper 2.0, is released with improved user interface and online map support.

MALÅ Easy Locators are robust, foldable GPR-systems with exceptional data collection capabilities for utility detection and subsurface anomaly locating. The MALÅ HDR real-time sampling technology means higher data resolution and significantly better depth of penetration compared to traditional GPR technology.

MALÅ EL Pro WideRange HDR Controller

Processor	1.6 GHz Intel Atom
Display	High Resolution 1024 x 768 pixels High contrast – Sunlight-readable
Operating system	Linux
Memory	8 GB compact Flash memory
Data output resolution	32 bit (*.rd7)
Comms	Ethernet, USB, RS232 (serial)
GPS	Built-in GPS in antenna (SBAS), support for external GPS
Power supply	10-15 V DC source
Operating time	Up to 8 hrs
Power consumption	1.3 – 1.8 A (depending on back-light settings)
Dimensions	L330 x W220 x H90mm, including handles
Weight	2.5 kg / 5.5 lbs
Operating temp	-20 °C to +50 °C / 0 °F to 120 °F
Environmental	IP 65



MALÅ EL Pro WideRange Antenna

Technology	MALÅ HDR Technology
Effective bandwidth	80-950 MHz
SNR	> 101 dB
Significant/useful number of bits	> 18 bit
Scans/second	> 500
Operating time	Up to 8 hrs
Positioning	Built-in DGPS (SBAS), external GPS, wheel encoder
Power supply	Interchangeable 12 V Li-Ion batt. or ext. 12 V DC source (hot-swap)
Power consumption	3 A
Acq. Mode	Wheel or manual
Dimensions	L720 x W480 x H190mm
Weight	10.8 kg / 23.8 lbs (including skidplate 11.8kg)
Operating temp	-20 °C to +50 °C / 0 °C to 120 °F
Environmental	IP 65

MALÅ EL Pro Cart Mk2

Dimensions, folded for transport	L820 x W695 x H420mm
Dimensions, when in use	L1060 x W695 x H1050mm
Weight	13 kg / 28.7 lbs
Battery compartment	Fits four 12 V Li-Ion

ABEM | MALÅ World Leading Brands

Guideline Geo is a world leader in geophysics and geo-technology offering sensors, software, services and support necessary to map and visualize the subsurface. Guideline Geo operates in four international market areas: Infrastructure – examination at start-up and maintenance of infrastructure, Environment – survey of environmental risks and geological hazards, Water – mapping and survey of water supplies and Minerals – efficient exploration. Our offices and regional partners serve clients in 121 countries. The Guideline Geo AB share (GGEO) is listed on NGM Equity.

GUIDELINE GEO

GUIDELINE GEO AB

Löfströms Allé 6A
SE-172 66 Sundbyberg, Sweden
Tel: +46 8 557 613 00
info@guidelinegeo.com
www.guidelinegeo.com

GUIDELINE GEO AMERICAS INC.

1270 Drop Off Drive, Unit B
Summerville, SC 29483 USA
Tel: +1 843 852 5021
sales@guidelinegeo.com
americas.guidelinegeo.com