



Easy Locator

WideRange HDR

The professional's choice for utility mapping

Technical Specification

The MALÅ Easy Locator WideRange is a professional work tool designed for efficient utility detection. With the widest GPR antenna bandwidth currently available in the market, the EL WideRange facilitates ultra-fast, simultaneous high-resolution data acquisition for both shallow and deep targets—all conveniently housed in a rugged cart solution.

Together with the MALÅ Rough Terrain Cart (RTC), the Easy Locator WideRange is adaptable to virtually any terrain. For an easy workflow, data is managed in MALÅ Vision. The software features cloud-based storage and processing, a user-friendly interface and direct reporting capabilities.

All MALÅ Easy Locators are robust GPR-systems with exceptional capabilities for utility detection and pinpointing subsurface anomalies. The Easy Locator WideRange is using MALÅ HDR, real-time sampling technology, giving higher data resolution and significantly improved depth of penetration compared to traditional GPR technology.



Easy Locator WideRange HDR Controller

Processor	1.6 GHz Intel Atom
Display	High Resolution 1024 x 768 pixels, High contrast – Sunlight-readable
Operating system	Linux
Memory	8 GB compact Flash memory
Data output resolution	32 bit (*.rd7)
Comms	Ethernet, USB, RS232 (serial)
GPS	Built-in GPS in antenna (SBAS), support for external GPS
Power supply	10-15 V DC source
Operating time	Up to 8 hrs
Power consumption	1.3 – 1.8 A (depending on back-light settings)
Dimensions	430 x 360 x 180 mm, including handles
Weight	2.5 kg / 5.5 lbs
Operating temp	-20 °C to +50 °C / 0 °F to 120 °F
Environmental	IP 65

Easy Locator WideRange Antenna

Technology	MALÅ HDR Technology
Effective bandwidth	80-950 MHz
SNR	> 101 dB
Significant/useful number of bits	> 18 bit
Scans/second	> 500
Operating time	Up to 8 hrs
Positioning	Built-in DGPS (SBAS), external GPS, wheel encoder
Power supply	Interchangeable 12 V Li-Ion batt. or ext. 12 V DC source (hot-swap)
Power consumption	3 A
Acq. Mode	Wheel, time or manual
Dimensions	720 x 480x 190 (L x W x H)
Weight	10,8 kg / 23.8 lbs
Operating temp	-20 °C to +50 °C / 0 °C to 120 °F
Environmental	IP 65

Rough Terrain Cart (RTC)

Weight	21 kg / 46,3 lbs, without controller or antenna mounted
Battery bay/compartament	Up to four standard MALÅ 12V batteries



Visit us at: www.guidelinegeo.com

GUIDELINEGEO

GUIDELINE GEO has been in the geophysics business since 1923 and is the global leader in near-surface geotechnology. Our advanced technology ensures practical solutions to everyday, societal, and global problems. We deliver total solutions in the technological fields of ground penetrating radar, seismic, geoelectrical and electromagnetic measurement. The Guideline Geo AB share (GGEO) is listed on Nasdaq First North Growth Market. We are a Swedish company with international offices and regional partners serving clients in over 100 countries.